

PA - 295 Flooring Adhesive Part A & B

Description

Protect-All® PA-295 is a two-part urethane adhesive designed for use in the installation of Protect-All flooring. This high-performance adhesive is ideal for installations in high-traffic areas over concrete slabs with very high moisture content. Featuring remarkable shear strength, PA-295 is an excellent solution for applications that require maximum resistance to heavy foot traffic and rolling loads. PA-295 requires no flash time, meaning installation can begin immediately.

Characteristics

- No-slump formula
- Zero VOC's
- Indoor moisture up to 25 lbs. MVER
- 95% in-situ RH
- Coverage rate: 70 - 80 sf/gal
- Cure time: 12 hours



Preparation and Installation

- Thoroughly mix part B into part A until it has achieved a consistent color mix
- Spread using a 1/8" x 1/8" x 1/16" V-notch trowel
- Can be welded after 12 hours
- Light foot traffic after 12 hours

Protect-All flooring should be installed by a factory-trained installer only.

Please refer to the Protect-All installation guide on our website for full instructions on how to properly apply PA-295.

Open Times	30% RH	50% RH	80% RH
50° F / 10° C	90 mins	90 mins	90 mins
70° F / 21° C	75 mins	75 mins	75 mins
90° F / 32° C	60 mins	60 mins	60 mins